

## Product Profile



### E A S Y C O D E R P D 4 1

- **Best performance in its class – prints at 6 ips continuously**
- **Best print quality in its class – crisp & clear labels even at full printing speed**
- **Metal chassis and covers, proven mechanics**
- **User friendly design, simple one-button operation**
- **Many features at an affordable price**
- **Multi-lingual capability, adapts to host environment changes**
- **Unicode printing support – wide selection of fonts, including many non-Latin**

The EasyCoder PD41 is a dependable and versatile printer suitable for medium-duty applications in manufacturing, transportation and warehousing environments. With all-metal chassis and covers, proven printing mechanics and powerful electronics, it provides the sturdiness and performance your business depends on.

The EasyCoder PD41 can print demanding crisp variable-data labels continuously at 150 mm/s (6 ips), thereby outperforming all other printers in its class. It takes industry-standard 200-mm (8-in) rolls of labels and 450 m (18 000 in) of ribbon, reducing downtime for loading media to a minimum. The printer accepts a wide range of paper types in different thicknesses, as well as both ink-in and ink-out ribbon.

In addition the EasyCoder PD41 offers many Smart Printing™ features normally found only in high-performance printers. Multi-language capability and Intermec Ready-to-Work™ indicator are standard – all at an affordable and competitive price.

Networking is an increasingly important user requirement but still a rare feature in this printer class.

The EasyCoder PD41 offers EasyLAN™ high-speed, multi-channel Ethernet as a standard choice.

PrintSet™, a PC-based setup tool, makes installation and setup of the EasyCoder PD41 intuitive and easy. The one-button interface makes the printer easy to operate and well protected against unintentional changes of the setup. An open and accessible design makes media loading quick and easy, and the printhead can easily be replaced without using any tools.

The ability to use any Intermec printer language and emulate other printer protocols makes the EasyCoder PD41 both fully compatible with other Intermec equipment and a cost-effective “drop-in” printer replacement in almost any non-Intermec firmware environment. Featuring full programmability (using Fingerprint), the EasyCoder PD41 can change with the application. There’s no need to replace the printer when you upgrade your firmware environment – the printer will adapt.

The EasyCoder PD41 keeps your options open and protects your investment.

**Application**

Direct Thermal and Thermal Transfer label, ticket and tag printing

**Physical Characteristics**

**Length:** 453 mm (17.8 in)  
**Height:** 273 mm (10.8 in)  
**Width:** 270 mm (10.6 in)  
**Weight:** 13 kg (28.7 lbs)

**Print Specifications**

**Max. Width:** 104 mm (4.09 in) at 203 dpi  
 105.7 mm (4.16 in) at 300 dpi  
**Max. Length:** 1520 mm (59.8 in) at 203 dpi  
 1028 mm (40.5 in) at 300 dpi

**Print Speed**

50-150 mm/s (2-6 ips) at 203 dpi  
 50-100 mm/s (2-4 ips) at 300 dpi

**Print Direction**

Prints smooth text, any size bar codes and graphics in all four orthogonal directions.

**Print Resolution**

- 8 dots/mm (203 dpi)
- 12 dots/mm (300 dpi, option)

**Label/Ticket/Tag**

**Width:** 25-118 mm (1.00-4.64 in)  
 25-114 mm (1.00-4.48 in with cutter)  
**Thickness:** 60-250 µm (2.3 to 9.8 mil)  
**Style:** Roll-fed, die-cut, continuous or fanfold labels, tags or tickets  
**Label Roll max. diameter:**  
 213 mm (8.35 in)  
 190 mm (7.5 in) with internal rewinder (full roll of liner/backing paper)  
**Label Roll Core:** 37.5 or 75 mm (1.5 or 3 in)  
**Media Type:** Direct Thermal or Thermal  
**Transfer media:** Roll-fed, Fanfold and Continuous

**Ribbon**

**Max. Ribbon Length:** 450 m (18 000 in)  
**Ribbon Roll Core Diam:** 25,4 mm (1.0 in)  
**Ribbon Width:** 30-110 mm (1.18-4.33 in)  
**Winding Direction:** Ink-in or Ink-out

**Sensors**

- Adjustable Gap, Blackmark and Punched Hole sensors
- Out-of-Media sensor
- Out-of-Ribbon sensor
- Label Taken sensor

**Interfaces****Standard:**

- Serial RS-232
- USB v. 2.0 full speed
- Parallel or EasyLAN Ethernet (depending on configuration)

**Optional:**

- Parallel IEEE 1284 or
- EasyLAN integrated Ethernet: RJ-45 connector for 10BaseT or 100baseTX

**Supported Protocols:**

TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMP, SMTP, SNMP-MIB II supported (over UDP/IP), private enterprise MIB included

**Software**

- InterDriver™ Windows printer drivers with ActiveX Controls
- Intermec LabelShop® START label design and print package
- PrintSet for printer configuration
- IPNM (Intermec Printer Network Manager) for administration of network connected printers

**Bar Code Symbolologies**

**1-dimensional:** Codabar, Code 11, Code 39, Code 39 full ASCII, Code 39 w. checksum, Code 93, Code 128, Code 128 Subset A-C, DUN-14/16, EAN-8, EAN-13, EAN-128, EAN-128 Subset A-C, Five-Character Supplemental Code, Industrial 2 of 5, Industrial 2 of 5 w. checksum, Interleaved 2 of 5, Interleaved 2 of 5 w. checksum, Matrix 2 of 5, Postnet, Straight 2 of 5, Two-Character Supplemental Code, UCC-128 Serial Shipping Container Code, UPC-5 digits Add-On Code, UPC-A, UPC-D1 to D5, UPC-E, UPC Shipping Container Code, RSS, Planrt, Plessey  
**2-dimensional:** Code 16K, Code 49, Data Matrix, MaxiCode, MSI (modified Plessey), PDF 417, QR Code, MicroPDF417, EAN.UCC Composite

**Character Sets**

15 TrueDoc™ scalable fonts including 12 UNICODE (1 WGL4 including Latin, Baltic, Cyrillic, Greek and Turkish characters), 1 symbol, 1 OCR-A, 1 OCR-B. Font cache for maximum performance. ATF font support. Asian, Hebrew and Arabic fonts available as option

**Graphics**

Supports PCX file format, traditional BT201 Intelhex format and High-Speed Image Buffer printing

**Memory**

**Standard:** 4 MB Flash memory  
 8 MB SDRAM (1 Compact Flash slot)  
**Optional:** Up to 1 GB CompactFlash (type 1) memory

**Keypad Control Panel**

One Print/Pause button  
 Four LED indicators; Power, Data Transfer, Error/Warning, Ready-to-Work

**Power Supply**

**Voltage Range:**  
 100-240 VAC ±10% auto switch  
**Frequency Range:** 45-65 Hz

**Operating Environment**

**Temperature:** +5°- 40°C (+40°- 104°F)  
**Humidity:** 20-85% non-condensing free air

**Regulatory Approvals**

FCC, UL, cUL, CE, NOM

**Field Installable Options**

Internal Rewinder, Cutter, CompactFlash Memory Cards, Parallel Interface, EasyLAN integrated Ethernet interface



**North America Corporate Headquarters**  
 6001 36th Avenue West  
 Everett, Washington 98203  
 tel.: 425 348 2600  
 fax: 425 355 9551

**Systems & Solutions**  
 550 2nd Street S.E.  
 Cedar Rapids, Iowa 52401  
 tel.: 319 369 3100  
 fax: 319 369 3453

**Media Supplies**  
 9290 Le Saint Drive  
 Fairfield, Ohio 45014  
 tel.: 513 874 5882  
 fax: 513 874 8487

**Canada**  
 7065 Tranmere Drive  
 Mississauga, Ontario  
 L5S 1M2 Canada  
 tel.: 905 673 9333  
 fax: 905 673 3974

**Europe/Middle East & Africa Headquarters**  
 Reading International  
 Business Park  
 Basingstoke Road  
 Reading  
 Berkshire RG2 6DD  
 United Kingdom  
 tel.: +44 118 923 0800  
 fax: +44 118 923 0801

**Benelux**  
 Intermec Technologies  
 Benelux BV  
 P.O. Box 40223  
 NL-6504 AE Nijmegen  
 The Netherlands  
 tel.: +31 24 372 31 00  
 fax: +31 24 372 31 95  
 www.intermec.nl

**Denmark**  
 Intermec Technologies AS  
 Gydevang 21 A  
 DK-3450 Allerød  
 Denmark  
 tel.: +45 48 166 166  
 fax: +45 48 166 167  
 www.intermec.dk

**France**  
 Intermec Technologies SA  
 Immeuble « Le Newton »  
 23 Avenue de L'Europe  
 F-78402 Chatou Cedex  
 France  
 tel.: +33 1 30 15 25 35  
 fax: +33 1 34 80 14 33  
 www.intermec.fr

**Germany**  
 Intermec Technologies  
 GmbH  
 Schiess-Straße 44a  
 40549 Düsseldorf  
 Germany  
 tel.: +49 211 536 010  
 fax: +49 211 536 0150  
 www.intermec.de

**Italy**  
 Intermec Technologies SRL  
 Via Cialdini 37  
 20161 Milano  
 Italy  
 tel.: +39 02 66 24 051  
 fax: +39 02 66 24 05 58  
 www.intermec.it

**Norway**  
 Intermec Technologies A/S  
 Solheimsveien 91F  
 Postbox 217  
 N-1471 Skårer  
 Norway  
 tel.: +47 67 91 17 10  
 fax: +47 67 91 17 11  
 www.intermec.no

**Spain & Portugal**  
 Intermec Technologies SA  
 Ronda de Valdecarrizo, 23  
 28760 Tres Cantos-Madrid  
 Spain  
 tel.: +34 91 806 0202  
 fax: +34 91 804 2221  
 www.intermec.es

**Sweden**  
 Intermec Technologies AB  
 Vendevägen 85A  
 S-182 91 Danderyd  
 Sweden  
 tel.: +46 8 622 06 60  
 fax: +46 8 622 06 61  
 www.intermec.se

**United Kingdom**  
 Intermec Technologies  
 UK Ltd.  
 Reading International  
 Business Park  
 Basingstoke Road  
 Reading  
 Berkshire RG2 6DD  
 United Kingdom  
 tel.: +44 118 923 0800  
 fax: +44 118 923 0801  
 www.intermec.co.uk

**Worldwide Fax Document Retrieval Service**  
 800.755.5505  
 (North America 800)  
 tel.: 650.556.8447

**Internet**  
 www.intermec.com

**Sales**  
 800.347.2636  
 (toll free in N.A.)  
 tel.: 425.348.2726

**Service and Support**  
 800.755.5505  
 (toll free in N.A.)  
 tel.: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.K. 611706-01A 12/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.