



# HT 200e



## The Stand-alone Label Specialist The SATO HT200e

The innovative, stand-alone HT 200e printer is the perfect low cost solution, for both retail and industrial applications. With ready-made formats, automatic calculations and touch of a button printing, this printer is fast and very user-friendly.

- **Direct thermal**
- **Stand alone or online**
- **Automatic calculations**
- **Optional battery pack**
- **Easy label loading**
- **Simple to use**
- **Easy to program**

**Stand-alone** – There is no need for a PC with the HT200e, this printer is stand-alone, printing labels at the touch of a button.

**Portable** – The HT 200e can be run directly from the mains or from the rechargeable battery. The carry handle also means the printer is easy to transport.

**Simple to use** – Easy label loading, ready-made formats and automatic calculations make the HT200e very user-friendly.

**Easy to program** – For those wishing to design their own formats, programming is very straightforward and the memory large enough to store your personal designs.

**Applications** – Retail price marking, medical and pharmaceutical labelling, bakeries, cosmetics, stock control and item identification.

# HT200e

HT200e	
<b>Printing Method</b>	Direct or Thermal Transfer
<b>Print Resolution</b>	8 dots/mm (203 dpi)
<b>Print Speed</b>	Up to 60mm/sec (2.3 ips) battery operated or up to 80mm/sec (3.1 ips) AC Adapter
<b>Max. Print Width</b>	48mm (1.89")
<b>Max. Print Length</b>	96mm (3.78")
<b>Media Size</b>	Min. 28mm (1.1") W x 16mm (0.63") L Max. 51mm (2") W x 103mm (4") L
<b>Dimensions</b>	132mm W x 230mm D x 151mm H (5.2" W x 9.06" D x 5.94" H)
<b>Weight</b>	2.4kg (5.3lbs) with battery pack or 2.5kg (5.5lbs) with power supply

#### Features:

- Auto Power off (5 min)
- Calendar (standard)
- Back lit LCD  
(16 characters x 3 lines)

#### Memory:

- 512K Bytes SRAM
- 2 MB SRAM Card (option)

#### Processor:

- 32-Bit RISC, 60Mhz

#### Media:

- Caliper: 0.14 – 0.19mm (5.5 – 7.48MIL)
- Core diameter: 26.5mm (1")
- Max. Roll O.D: 75mm (2.95")

#### Sensing:

- Transmissive sensor for gaps
- Reflective sensor for I-Marks

#### Interface Connection:

- RS232C Serial Interface  
Scanner (RS232C)

#### Bar Code Symbologies:

UPC-A/-E, EAN-8/13, Code 39,  
Code 128, I2/5

#### Bar Code:

2:1, 2.5:1, 3:1 ratio;  
bar code height 1 to 240 dots

#### Human Readable Fonts:

8 fonts including 4 useful  
POP characters.  
Code Pages 858 and 852

#### Rotation:

- Font: 0°, 90°, 180°, 270°
- Bar code: 0°, 180°

#### Self Check Function:

Paper End; Cover Open; Test Print;  
Battery Level Check; Head Check

#### AC Power:

- AC 230V +/-10%; Voltage + 8.4V
- Consumption: Max. 71VA 43W

#### Options:

Battery Pack & Charger,  
SRAM Card (2MB), Label Rewinder  
Touch or Pen Scanner



Labelgraphics (Glasgow) Limited  
Unit 1, 2 South Avenue, Clydebank Business Park  
Glasgow G81 2LE Scotland  
Tel: +44(0) 141 952 9600  
Fax: +44(0) 141 951 1775  
E-Mail: systems@labelgraphics.co.uk  
Web: www.labelgraphics.co.uk



SATO makes no guarantee that the above features are available in all models, and specifications are liable to change, without notice.